



BASS G15

Bass reflex passive subwoofer European transducer 15" LF (4in)



Presentation:

The BASS series offers a professional passive subwoofers range becoming the perfect choice for sound reinforcement challenges demanding high SPL and natural-sounding bass response designed to enhance the ultra-low bass of an existing PA system. Both models are on bass reflex configuration and constructed of 18mm birch plywood featuring 15" loudspeakers with 4" voice coil delivering a nominal power handling of 700W rms at 8 Ohms each giving low-ranging yet clearly defined bass response and rendering impulses with great accuracy in a very compact and robust enclosure. Punch and bass sensation do not have to be incompatible factors and this BASS series truly is a great example

Features:

- Bass reflex subwoofer
- 15" (4in) LF European transducer
- 1200W AES power, 4800W peak
- Dual Neutrik NL4 connectors
- Optimized for high SPL output
- Made for an impact bass
- Recesses on the top to facilitate the stacking
- Rugged and durable 18mm birch plywood
- Powder coated custom perforated steel grille

Other pictures:



Front view



Side view



Rear view



Persp Rear view





BASS G15

Bass reflex passive subwoofer European transducer 15" LF (4in)

Technical specifications:

Acoustical

Type Compact passive subwoofer

Configuration Reflex Loaded
Power handling capacity 1200W (AES)
4800W (Peak)

Transducer type. 1x 15" (4in) LF European transducer

Frequency response 32Hz - 250Hz (-10dB)
Recommended Low cut filter 35Hz Butterworth 18dB

Nominal Impedance 8 Ohm

SPL (1W/1kHz) 126dB @ 1m (continuous)

132dB @ 1m (peak)

Connectors 2x NL4 connectors

Physical

Cabinet 18mm birch plywood with polyurea coating
Grille Custom perforated metal grille w/ acoustic foam

Color Black or white textured

Hardware/Rigging 4 wood feet, Ø35mm pole mount socket

2 side metal handles, 16x M6 inserts for castors

Dimensions 590x452x635mm

23.23x17.79x25.00in

Weight 32Kg 70.55lb

Dimensions:

BASS G15 // G15A



