PROUDLY DEVELOPED AND MANUFACTURED IN PORTUGAL

BASS G18 Bass reflex passive subwoofer European transducer

18" LF (4in VC)



Presentation:

The BASS series offers a professional passive subwoofers range becoming the perfect choice for sound reinforcement challenges demanding high SPL and natural-sounding bass response designed to enhance the ultra-low bass of an existing PA system. Both models are on bass reflex configuration and constructed of 18mm birch plywood featuring 18" loudspeakers with 4" voice coil delivering a nominal power handling of 1000W rms at 8 Ohms each giving low-ranging yet clearly defined bass response and rendering impulses with great accuracy in a very compact and robust enclosure. Punch and bass sensation do not have to be incompatible factors and this BASS series truly is a great example

Features:

PROFACTOR S.A. reserve the right to change the specification

- Bass reflex subwoofer
- 18" (4in) LF European transducer
- 1200W AES power, 4800W peak
- Dual Neutrik NL4 connectors
- Optimized for high SPL output
- Made for an impact bass
- Recesses on the top to facilitate the stacking
- Rugged and durable 18mm birch plywood
- Powder coated custom perforated steel grille

Other pictures:



Front view



Side view



Rear view



Persp Rear view

∑ (€





PROUDLY DEVELOPED AND MANUFACTURED IN PORTUGAL

BASS G18

Bass reflex passive subwoofer European transducer 18" LF (4in VC)

Technical specifications:

Acoustical

Type Configuration Power handling capacity

Transducer type Frequency response Recommended Low cut filter Nominal Impedance SPL (1W/1kHz)

Connectors

Physical

Cabinet	
Grille	18mm birch plywood with polyurea coating
Color	Custom perforated metal grille w/ acoustic foam
Hardware/Rigging	Black or white textured
	4 wood feet, Ø35mm pole mount socket
	2 side metal handles, 16x M6 inserts for castors
Dimensions	750x540x710mm
	29.53x21.26x27.95in
Weight	41Kg
	90.39lb

Compact passive subwoofer

1x 18" (4in) LF European transducer

Reflex Loaded

27Hz - 200Hz (-10dB)

35Hz Butterworth 18dB

128dB @ 1m (continuous) 134dB @ 1m (peak)

2x NL4 connectors

1200W (AES) 4800W (Peak)

8 Ohm

Dimensions:

BASS G18 // G18A

