

# C1205DP

Active full range column speaker 100W / 80hm output



## Presentation:

Line source speaker system especially developed for difficult acoustic conditions with long reverberation times such as churches, museums, conference rooms, etc. This DIGI series features ultra-quiet and highly efficient Class D amplifiers (3x 75W rms) in two different models driven by 5" rubber cone transducers and 1" compression drivers to increase speech intelligibility especially in reverberant rooms. With an integrated DSP module all functions needed to adjust and to complete an installation are available by remote control through the RJ45 cable coupled to a PC (software), enabling very precise energy dispersion manipulation to achieve a perfectly adapted sound system that fulfils all requirements of a modern speaker system regarding design, sound quality and operating comfort in every respect. Thanks to their aluminum housings, this DIGI vertical array speaker series is genuine lightweights, yet at the same time extremely robust, perfectly suited for speech and background music transmissions.

### Features:

- Line source installation speaker
- Ideal for difficult acoustic environments
- Superb speech intelligibility
- 12x 5" MF + 1" HF transducers
- Driven by Class D amplifier
- Built-in DSP technology
- Computer remote controllable, network ready
- Rugged and solid aluminum construction
- Supplied with C-sup L for wall mount

## Other pictures:



### Technical specifications:

## Acoustical

Configuration Active full range column speaker
Power handling capacity 150W + 50W + 100W rms
Elements 12x 5" rubber cone + 1" HF driver
Frequency response 90Hz - 18kHz
Horiz./Vert. coverage angle 120° / 30°
Max. SPL 90dB @ 1m

Dynamic

#### **Electronics**

HF protection

Amplifier type Class D (digital)

Amplifier output 150W + 50W + 100W / 40hm

Audio input Balanced XLR 3p male

Audio output Balanced XLR 3p female

100W / 80hm for speaker

AC Mains AC 230V. 50/60Hz

## Physical

Weight

Cabinet Extruded aluminium construction

Grille Custom perforated metal grille

Color Black or white textured powder coating

Hardware C-sup L for wall mounting

Dimensions 1850x185x155mm

22.5Kg

**₹ (€**