

# PROUDLY DEVELOPED AND MANUFACTURED IN PORTUGAL

Public address speaker 100V line input



## Presentation:

Range of public address passive speakers in a lightweight AL profile. Both C8 and C16 column speakers are constructed in a narrow aluminum profile featuring 1.5" rubber cone transducers while C104/C204/C404 and C604 feature 4" transducers, all with an integrated 100V line transformer allowing multiple speakers to be connected together without danger of overloading the power amplifier due to impedance drop. All models are supplied with wall mount supports/brackets, available in 2 colors: black and white. This range of speakers is the perfect solution for all kind of public address installations, designed to offer a cost effective but professional solution, suited for installations such as conference rooms, congress centers, supermarkets, shopping malls, etc.

#### Features:

- Public address installation speaker
- Cost-effective solution for installations
- 8x 1.5" rubber cone transducer
- Suitable for 100V high imp. installations
- Ultra slim and elegant aluminum profile
- Custom perforated metal grille
- Textured powder coating finishing
- Supplied with C-sup S support for wall mount

#### Other pictures:



Technical specifications:

### Acoustical

Configuration Power handling capacity LOW/MID freq. Frequency response

Horinzal coverage angle Vertical coverage angle SPL (1W/1kHz) High impedance input

Connector

Physical

Cabinet Grille Color Hardware Dimensions Weight Public address column speaker 15W rms 8x 1.5" rubber cone woofer 100Hz - 15kHz 120° 30° 88dB @ 1m 100V line transformer Terminal - screw type

Extruded and solid aluminum construction Custom perforated metal grille Black or white textured powder coating C-sup S for wall mounting 57x55x375mm 1Kg

