




MOOSE
www.moosesound.com

PROUDLY DEVELOPED AND
MANUFACTURED IN PORTUGAL

INSTALL i6

Installation speaker
Speakon & Euroblock
Wall mount support




Presentation:

The Installation series speakers is the right choice to anyone that wants to install loudspeakers into a wall or into a ceiling matching the high quality sound requirements for modern indoor spaces. Extremely compact, accurate and good looking the 2-way speakers can also be complemented with a number of MOOSE subwoofer systems. The range comprises 3 models of 5", 6" and 8" incorporating high quality European transducers combined with an extremely high sensitivity and lower distortion Phenolic supertweeter for outstanding detail and clarity in high frequencies without harshness and bullet-shape horn design to offer a long throw. All speakers feature an internal passive crossover designed to deliver neutral and natural sound and a line transformer can be installed (optional). MOOSE Installation series speakers feature Neutrik NL4 connectors and Euroblock speaker terminal parallel-connected for an easy and flexible installation regardless the surroundings. Only the i8 features pole-mount socket which can be easily pole mounted wherever you need extra monitor or fill sound. All models are prepared to be wall mounted having two types of mounting brackets available, one for vertical (portable) and another for horizontal installation (permanent) depending on the application and location. The I series range is available matched to any RAL colour suited for a variety of venues including restaurants, bars, clubs, retail shops, exhibition centers, fitness centers, conference rooms ensuring maximum speech intelligibility, precise band coverage and ease of installation thanks to the flexible mounting hardware solutions, wall and "U" brackets.


Features:

- 2-way passive installation speakers
- 6" (1,26in) MF EU transducers
- High sensitivity 1" Kapton driver
- NL4MP® and Euroblock speaker terminals
- Optional line transformer (adding "T")
- Elegant, refined and lightness design
- "U" Wall-mount brackets, hor. and vert. install
- Wall-mount support adjustable in 2 axes
- Rugged and durable 12mm birch plywood

Other pictures:



Front View



Side View



Rear view





MOOSE
www.mooseound.com

PROUDLY DEVELOPED AND
MANUFACTURED IN PORTUGAL

INSTALL i6

Installation speaker
Speakon & Euroblock
Wall mount support

Technical specifications:

Acoustical


Type	2-way passive installation speaker
Enclosure design	Bass reflex
Power handling capacity	140W (RMS) 280W (Program)
Frequency range	80Hz - 18kHz
Transducer type	6" MF (126in) EU transducer 1" HF kapton EU transducer
Dispersion	80° conical, aluminum horn
Crossover frequency	2500Hz
SPL max. (1W/1kHz)	116dB @ 1m
Connectors	2x Neutrik® NL4 in parallel Phoenix® Euroblock, 4 pole, speaker terminal

Physical


Cabinet	12mm birch plywood, rugged watertex coating
Grille	Custom perforated metal grille w/ acoustic foam
Color	Black or white textured
Hardware	4x M6 inserts for "U" bracket (supplied)
Dimensions	4x M5 inserts for wall mount/ceiling support, 2-axes (optional) 210/155x300x230mm / 8.27x11.81x9.06in
Weight	6.0Kg / 13.22lb

Dimensions:

INSTALL
i6



ACCESSORIES
WSI



ACCESSORIES
WB6

