

MOOSE

www.moosesound.com

PROUDLY DEVELOPED AND
MANUFACTURED IN PORTUGAL

GROOVE M15

Wedge stage monitor
90°x60° rotatable horn
Active version available




Presentation:

The GROOVE series stage monitors are not just powerful, accurate, compact but beautifully designed. The series has been engineered to deliver a complete sound reinforcement solution to fulfil the highest demands of audio professionals for both permanent installation and rental production markets. The GROOVE series comprises a 10" (2in), 12" (2.5in) and 15" (2.5in) formats incorporating LF loudspeakers that combines excellent linearity with good sensitivity and power handling characteristics together with a 1" (1.73in) compression driver coupled to a CD rotatable (90°x60° and 60°x90°) horn and an internal passive crossover resulting in a surprising sonic performance inside a compact package. The active versions are equipped with a class D amplifier and a fully programmable DSP 48kHz (user friendly software) for real time operation according to different environments and music styles. With 5 presets that can be loaded on the rear panel, the class D amplifier is prepared for 85-264Vac universal mains and features various electronic protections to guarantee the use of the speaker system in perfect sound and safe operation. To make it portable and flexible, there is a pole mount socket in one side. As a high performance stage monitor, the GROOVE series is suited to sound reinforcement applications such as front of house, floor monitor, sidefill monitoring small and medium sized stages as well as distributed systems.


Features:

- Professional wedged stage monitor
- Passive and active versions available
- 15" MF + 1" HF European transducers
- 8 Ohm passive
- Dual Neutrik NL4 connectors
- Pole mount fitting for stand support
- Elegant looking professional enclosure
- Rugged and durable 15mm birch plywood
- Powder coated custom perforated steel grille

Other pictures:



Front view



Rear view




Side view



Perspective rear view





MOOSE

www.mooseaudio.com

PROUDLY DEVELOPED AND
MANUFACTURED IN PORTUGAL

GROOVE M15

Wedge stage monitor
90°x60° rotatable horn
Active version available

Technical specifications:

Acoustical

Type	2-way passive stage monitor
Enclosure design	Wedge shape
Power handling capacity	410W (RMS) 560W (Program) 1100W (Peak)
Frequency range	65Hz - 19kHz
Nominal impedance	8Ohm
Transducer type	15" MF (2.5in) EU transducer 1" HF (1.73in) EU transducer
Dispersion	90°x60° or 60°x90° rotatable horn
Crossover frequency	2.0kHz
SPL max. (1W/1kHz)	129dB @ 1m
Connectors	2x Speakon NL4 (parallel)

Physical

Cabinet	15mm birch plywood, rugged polyurea coating
Grille	Custom perforated metal grille w/ acoustic foam
Color	Black textured
Hardware	4 rubber feet, Ø35mm pole mount insertion
Dimensions	750x350x540mm 29.53x13.75x21.26in
Weight	22Kg 48.5lb

Dimensions:

GROOVE
M15

