

C404

Public address speaker 100V line input



Presentation:

Range of public address passive speakers in a lightweight AL profile. Both C8 and C16 column speakers are constructed in a narrow aluminum profile featuring 1.5" rubber cone transducers while C104/C204/C404 and C604 feature 4" transducers, all with an integrated 100V line transformer allowing multiple speakers to be connected together without danger of overloading the power amplifier due to impedance drop. All models are supplied with wall mount supports/brackets, available in 2 colors: black and white. This range of speakers is the perfect solution for all kind of public address installations, designed to offer a cost effective but professional solution, suited for installations such as conference rooms, congress centers, supermarkets, shopping malls, etc.

Features:

- Public address installation speaker
- Cost-effective solution for installations
- 4x 4" FR transducer
- Suitable for 100V high imp. installations
- Solid and elegant aluminum construction
- Custom perforated metal grille
- Textured powder coating finishing
- Supplied with wall mount "L" brackets

Other pictures:



Technical specifications:

Acoustical

Configuration Public address column speaker

Power handling capacity 30W rms
LOW/MID freq. 4x 4" woofer
Frequency response 120Hz - 18kHz

Horinzal coverage angle 120°

Vertical coverage angle 30°

SPL (1W/1kHz) 97dB @ 1m

High impedance input 100V line transformer Connector Terminal – spring type

Physical

Cabinet Extruded and solid aluminum construction
Grille Custom perforated metal grille
Color Black or white textured powder coating

Hardware Wall mount "L" bracket
Dimensions 125x5x545mm

Weight 4.5Kg

₹(€