
The GROOVE M15 stage monitor incorporates a 12" (2.5" VC) LF loudspeaker that combines excellent linearity with good sensitivity and power handling characteristics together with a 1" (1.73in) compression driver coupled to a CD rotatable (90°x60° and 60°x90°) horn and an internal passive crossover network resulting in a surprising sonic performance inside a compact package.


To make it flexible, there are M8 and M10 inserts for wall and truss mounting.

As a high performance stage monitor, the GROOVE series is suited to sound reinforcement applications such as front of house, floor monitor, sidefill monitoring small and medium sized stages as well as distributed systems.




## Features:

- Multipurpose 2-way stage monitor
- Bass reflex wedged enclosure
- 15" (2.5in VC) MF + 1" (1.73in VC) HF EU transducers
- User-rotatable CD horn 90°x60° for ideal dispersion
- 2x NL4 parallel-connected
- $\,\blacksquare\,$  Prepared for wall and truss mounting
- lacktriangle Elegant looking professional enclosure
- Rugged and durable 15mm birch plywood, polyurea coating











Dimensions in mm [in]

## Technical specifications:

## Acoustical

Type 2-way passive stage monitor
Enclosure design Wedged cabinet - bass reflex

Power rating (RMS/Peak) 410W / 1600W Frequency range 50 - 19kHz (10dB)

Nominal impedance 8 ohm

Transducer type 15" MF (2.5in VC) EU transducer

1" HF driver (1.73in VC) EU transducer

Dispersion CD horn, 90°x60° and 60°x90° user-rotatable

Crossover frequency 2000Hz
SPL (IW/1kHz) 129dB @ 1m
Sensitivity 96dB

Connector 2x NL4 parallel-connected

## Mechanical

Enclosure 15mm birch plywood, rugged polyurea coating
Grille Custom perforated metal grilles w/ acoustic foam

Color Black or white textured

Hardware 4 rubber feet

Side handles, 4x M8 inserts + 2x M10 inserts

Prepared to fit a "U" bracket

Dimensions 730x485x360mm | 28.74x19.09x14.17in

Weight 25Kg | 55.16lb